

PRODUCTS SPECIFICATIONS

	22615 XTC	22900 XTC	22610 XTC	23610 XST	23030 PVMO	23001 PVMO	23010 PVMO	23020 PVMO	29500 XHD	35000 HDDO	34000 HDDO	57100 ATF	57105 XTF	75515 XTG
SAE Grade	0W30	5W20	5W40	5W40	5W20	5W30	10W30	10W40	5W40	15W40	15W40	ATF	ATF	75W90
Gravity, °API	35	35	34.5	34.5	32.5	32.3	31.1	30.1	34.8	31.1	30.1	33	33.9	31.1
Flash Point (°C)	200	200	200	200	221	223	229	229	200	229	226	179	204	199
Pour Point (°C)	(-42)	(-39)	(-46)	(-40)	(-39)	(-39)	(-33)	(-33)	(-45)	(-33)	(-33)	(-48)	(-35)	(-50)
Viscosity cSt @ 40°C	63.0	39.5	75.0	75.0	47.0	60.2	70.6	100.0	90.0	80.0	115.0	34.0	33.6	84.0
cSt @ 100°C	11.0	7.2	15.6	15.6	8.2	10.5	10.7	14.6	15.7	12.0	15.5	7.2	7.0	17.0
Viscosity Index	160	160	175	175	149	165	140	150	175	145	145	180	175	200
Colour	3.0	3.0	2.5	2.5	3.0	3.0	3.0	3.0	2.5	3.0	3.0	Red	Red	Green
Sulfated Ash, Wt.%	0.9	0.9	1.4	1.4	0.7	0.8	0.8	0.9	1.45	1.1	1.1	NA	NA	NA
Zinc, Wt.%	0.08	0.08	0.12	0.12	0.82	0.82	0.82	0.88	0.12	0.13	0.13	NA	NA	NA
Phosphorus, Wt.%	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	0.06	NA
TBN	7.6	7.6	12	12	7.5	7.5	7.5	7.5	12	9.7	9.7	NA	NA	NA
CSS	5,000	5,000	4,500	4,500	NA	NA	NA	NA	4,500	NA	NA	NA	NA	NA
Brookfield @ -40°F	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	10,800	NA
Available Packages	12 x 1L - - 208L -	12 x 1L - - 205L -	12 x 1L 6 x 4L - 208L -	12 x 1L - 60L 208L -	12 x 1L - - 205L Bulk	12 x 1L - - 205L Bulk	12 x 1L - - 205L Bulk	12 x 1L - - 205L Bulk	12 x 1L 6 x 4L - 208L -	12 X 1L - - 205L Bulk	12 x 1L 6 x 4L 20L 205L Bulk	12 x 1L - 20L 205L Bulk	12 x 1L - - 208L -	12 x 1L - - - -

NA Not available